

PRODUCT BENEFITS

- ▼ Dispensing with a gearbox means lower repair and maintenance costs and a higher yield.
- ▼ High-quality permanent magnets prevent electrical excitation losses, which additionally increases the energy yield.
- ▼ The air-cooling system used for the generator and the VENSYS frequency converter saves on additional components, cooling agents and maintenance work.
- ▼ The blade pitch system with a toothed belt drive is resistant to wear and requires little maintenance.

A detailed 3D rendering of a wind turbine nacelle, showing the internal components like the generator and frequency converter, and the three blades extending from the hub. The nacelle is white with a blue triangle logo on the side.

VENSYS 82

1.5 MW

VENSYS 82

1.5 MW



Operating data

Rated power	1.5 MW
Cut-in wind speed	3 m/s
Cut-out wind speed	22 m/s
Operating temperature	-20 °C to +40 °C

Sound power

Optimized for maximum performance	104.4 dB(A)
(Sound-reduced operating modes available)	

Rotor

Diameter	82.3 m
Swept area	5,320 m ²
Rotational direction	Clockwise
Rated speed	17.3 rpm
Blade type	EBT 40
Power control	Pitch
Primary braking system	Single-blade adjustment, triple redundant

Generator

Type	Synchronous generator with permanent magnet excitation
Construction type	Direct drive

Yaw system

Construction principle	Geared electric motors
Braking system	Hydraulic brake calipers

Converter

Type	IGBT full power converter
Frequency	50 Hz / 60 Hz

Tower

Hub heights	58 m 85 m 100 m
Material	Steel tube

Design

Hub heights (m) 58 85	IEC IIA
Hub heights (m) 58 100	IEC IIIA

POWER CURVE VENSYS 82

Wind speed m/s	AEP [MWh] VENSYS 82 - EBT 40
5.0	2,772.3
5.5	3,458.8
6.0	4,143.6
6.5	4,806.1
7.0	5,431.7
7.5	6,010.2
8.0	6,534.7
8.5	7,000.3

Power (kW)

