

## THE NEW 5S

- ▼ The ongoing reduction of energy costs will be continued with this platform
- ▼ Transport optimisation through segmented design of components
- ▼ Thirty years of experience using permanent magnet technology
- ▼ Low-wear and low-maintenance rotor blade pitch system
- ▼ Joint development with Goldwind

**5S** PLATFORM

# VENSYS 155

6.2 MW

# 5S PLATFORM VENSYS 155

6.2 MW

## Operating data

Rated power	6.2 MW
Cut-in wind speed	3 m/s
Cut-out wind speed	25 m/s
Operating temperature	-20 °C to +40 °C*

\*De-rating possible from 30 °C

## Sound power level

Optimized for maximum performance <106.0 dB(A)  
(Sound-optimised operating modes available)

## Rotor

Diameter	155.0 m
Swept area	18,869 m <sup>2</sup>
Rotational direction	Clockwise
Rated speed	9.1 rpm
Blade type	EBT 75.7
Power control	Pitch
Primary braking system	Single-blade adjustment, triple redundant

## Generator

Type	Synchronous generator with permanent magnet excitation
Construction type	Direct drive

## Yaw system

Construction principle	Geared electric motors
Braking system	Hydraulic brake calipers

## Converter

Type	IGBT full power converter
Frequency	50 Hz / 60 Hz

## Tower

Hub heights	102.5m   122.5m	Steel tube tower
	152.5 m	Hybrid tower (concrete / steel)

## Wind class

IEC IIA

## POWER CURVE VENSYS 155

Wind speed [m/s]	AEP [MWh] VENSYS 155 - EBT 75.7
5.0	9,711.1
5.5	12,289.7
6.0	14,925.9
6.5	17,537.5
7.0	20,063.7
7.5	22,462.0
8.0	24,704.1
8.5	26,770.8

